

THE DOCUMENT COMPANY

XEROX

DC230LP Banyan VINES® Quick Install

Installation Requirements:

Ensure that the PCPrint option has been installed and configured on your VINES server.

Before Installation:

Use the Banyan VINES MANAGE utility to:

- Create a StreetTalk Name and Password for the DC230LP.
- Create a Print Service Name for the DC230LP.
- Set the Destination to the StreetTalk Name.

The Destination Type for the DC230LP should be set to PCPRINT.






Record the following information for use during setup at the DC230LP:

StreetTalk Name: _____









StreetTalk Password: _____

Print Service Name: _____

This installation procedure assumes that you know how to navigate through the menu system on the DC230LP Control Panel. Refer to the quick reference card, *Using the Menu System*, (701P96834) for assistance.

1. Connect the DC230LP to your network outlet or cable.
2. Access the System Administration menus:
 - a) Press [**Online**] to take the printer off line.  displays.
 - b) Press [**Menu**].  displays.
 - c) Press [**▶**], then press [**▲**] or [**▼**] until  displays.
 - d) Press [**▶**].  displays.
 - e) Use the [**▲**] and [**▶**] keys to enter [**2222**].
 - f) Press [**Enter**].  displays.

Note: 2222 is the factory default password and may be changed to suit your needs. Refer to the *DC230LP System Administration Guide, Network Installation and Troubleshooting*.



3. Access the Banyan VINES setup:
 - a) Press [**▶**].  displays.
 - b) Press [**▼**] until  displays.
 - c) Press [**▶**].  displays.
 - d) Press [**▼**] until  displays.
4. Enable Banyan VINES:
 - a) Press [**▶**].  displays.
 - b) Press [**▶**].  displays.
 - c) Press [**▼**].  displays.
 - d) Press [**Enter**]. ****SAVED**** is displayed momentarily, followed by .


THE DOCUMENT COMPANY

XEROX


DC230LP Banyan VINES® Quick Install


5. Enter the StreetTalk name:

- a) Press [▼] until  displays.
- b) Press [▶].  displays.
- c) Press [▶] repeatedly until the cursor reaches the end of the entry. A tone sounds indicating when the last character has been reached.
- d) Press [◀] repeatedly to delete the current entry.
- e) Use the [▲] or [▼] key to select the first character in the Print Server Name.
- f) Press [▶] to move to the next character. Repeat this procedure to enter the entire Print Server Name.
- g) Press [Enter]. **SAVED** is displayed momentarily, followed by



6. Enter the StreetTalk Password:



- a) Press [▼] until  displays.

- b) Press [▶].  displays.


- c) Press [▶] repeatedly until the cursor reaches the end of the entry. A tone sounds indicating when the last character has been reached.
- d) Press [◀] repeatedly to delete the current entry.
- e) Use the [▲] or [▼] key to select the first character in the StreetTalk password.
- f) Press [▶] to move to the next character. Repeat this procedure to enter the entire StreetTalk password.
- g) Press [Enter]. **SAVED** displays momentarily, followed by



7. Enter the Print Service name:


- a) Press [▼] until  displays.
- b) Press [▶].  displays.
- c) Press [▶] repeatedly until the cursor reaches the end of the entry. A tone sounds indicating when the last character has been reached.

- d) Press [◀] repeatedly to delete the current entry.
- e) Use the [▲] and [▶] keys to enter the entire Print Service name.
- f) Press [Enter]. **SAVED** is displayed momentarily, followed by



8. Save all the settings:

- a) Press [Online].  displays.

- b) Press [Enter].  displays. The DC230LP will reboot, save the settings entered, and print a Configuration Report in approximately 3 minutes.

9. Check the settings on the Configuration Report against those entered in MAN-AGE. The StreetTalk password does not appear on the Configuration Report.

10. At the client, install print drivers and map the printer in the usual manner. For additional information, refer to the CentreWare® manual, *Getting Started with Print and Fax Services*, and the *DC230LP System Administration Guide, Network Installation and Troubleshooting*.