

# Banyan VINES Network Quick Install Card

## Xerox Document Centre 240/255/265 LP/ST

### Before You Start

If your printer is equipped with a Token Ring interface you must enable TCP/IP and use **lpr** to submit print jobs. Use the **Token Ring Quick Install Card** supplied in this Quick Install Card set to set the Ring Speed and Source Routing settings for your environment.

### Go to the printer and...

1. Connect your Document Centre to the network with the appropriate cabling.
2. Enter the *Tools* pathway
  - a) Press the **Access (A)** button.
  - b) On the keypad enter **1111** or the current password. Press the **Enter** button when finished. If your printer is an ST model press the **Go to Tools** button, otherwise skip to the next step.
  - c) The Touch Screen will be used for the remainder of the data entry.
3. Enable Banyan VINES printing.
  - a) Press the **Connectivity and Network Setup** button.
  - b) At the next screen, press the **Network Setup** button.
  - c) At the next screen, press the **Banyan VINES** button.

- d) At the next screen, press the **Protocol** button.
    - e) At the next screen, press the **Enable** button to start the Banyan Vines protocol and press **Save**.
  4. Configure User Name settings and Password.
    - a) At the next screen, press the **Settings** button.
    - b) At the next screen, press the **User Name/PC Print Destination** button, enter the desired text for this item using the touch panel keys, then press **Save**.
    - c) Press the **User Password** button, enter the desired text for this item using the touch panel keys, then press **Save**.
    - d) Press the **Print Service Name** button, enter the desired text for this item using the touch panel keys, then press **Save**.
    - e) Press the **Exit Tools** button.
  5. Wait a **MINIMUM of 7 minutes** for the printer to reset.
    - a) Obtain a **Configuration Report** page from your printer.

- b) Check the **Configuration Report** page and verify that **Banyan VINES** is enabled and the other Banyan Settings are correct.
  6. From the documentation package supplied with your printer, retrieve the **CentreWare Network Services CD-ROM** (CD-ROM 2) and the document entitled **Getting Started with Print and Fax Services**. Proceed to the next section of this procedure called **Go to the server and...**

# Banyan VINES Network Quick Install Card

## Xerox Document Centre 240/255/265 LP/ST

### Go to the server and...

1. Configure the Service and Queue.
  - a) Using the **MUSER** utility, create a user name and assign a password for the printer. The user name and password must be the same that were entered at the Document Centre.
  - b) Using the **MSERVICE** utility, highlight and select **ADD a server-based service**.
  - c) At the **Add A Service** screen, enter the **StreetTalk** name and **description** when prompted.
  - d) Select the server on which you want to create the service.
  - e) Select **Banyan Print Service**.
  - f) Select an appropriate disk location when prompted.
  - g) A message will be displayed stating that the service is running, but is not yet available to users.
  - h) Press the **F10** key to continue.
  - i) The **Configure Queue** screen will be displayed.
  - j) Press the **F10** key to accept the defaults.
2. Configure the Paper Formats.
  - a) The **Configure Paper Formats** Screen will be displayed.
  - b) Press the **Escape** key to continue without making any changes.
3. Configure Access Lists and Print Destination.
  - a) The **Access Lists** Screen will be displayed.
  - b) Press the **F10** key to accept the defaults.
  - c) The **Add a Destination** Screen will be displayed.
  - d) Select **PCPrint** and press **Enter**.
  - e) From the **Destination Attributes** Screen, enter the Document Centre user name as the PCPRINT ST name and Description, and then press the **F10** key.

---

Note The PCPrint ST name must be the same as the user name created and must also match the Street Talk (user) Name entered at the printer.

---
- f) The **Output Strings** Screen will be displayed. Press the **F10** key to accept the defaults displayed on the screen.
- g) The **Enable Strings** Screen will be displayed. Press the **F10** key to accept the defaults displayed on the screen.
- h) Select **No** and press **Enter** when you are prompted to add another destination.
4. Enable the Print Queue
  - a) The **Print Queue Status** screen will be displayed.
  - b) Change the **Printing jobs** and the **Accepting jobs** fields to **Yes** and then press the **F10** key.
  - c) A message will be displayed stating that the printer is ready to accept and print jobs. Press the **F10** key to continue.
  - d) The **Manage A Service** screen will be displayed.
  - e) Press the **Escape** Key to return to the **Manage Services** main menu.
5. Power off and power on the Document Centre 240/255/265 for these setup options to take effect.