



Welcome

 $\ensuremath{\mathbb{C}}$ 2005 Electronics for Imaging, Inc. The information in this publication is covered under Legal Notices for this product. 45051573 22 September 2005

WELCOME

This *Welcome* document provides system requirements and an overview of how to set up the Fiery EXP4110 so that you can begin printing. It describes the initial tasks you must perform and points you to sections in the user documentation where the procedures are described in further detail. This document also provides a description of the user documents on the User Documentation CD and instructions on printing them.

This document assumes that you have already installed the printer components. Details about the printer, the network, remote computers, software applications, and Microsoft Windows are beyond the scope of this document.

Terminology and conventions

This document uses the following terminology and conventions.

Term or convention	or convention Refers to	
Aero	Fiery EXP4110 (in illustrations and examples)	
Fiery EXP4110	Fiery EXP4110	
Mac OS	Apple Mac OS X	
Printer	Xerox 4110	
Titles in italics	Other documents in this set	
Windows	Microsoft Windows 2000, Windows XP, Windows Server 2003	
7	Topics for which additional information is available by starting Help in the software	
***	Tips and information	
\triangle	Important information	
A	Important information about issues that can result in physical harm to you or others	

About the documentation

This document is part of a set of documentation provided to users and system administrators of Fiery EXP4110. The documents are on the User Documentation CD and are in PDF (Portable Document Format). These files can be viewed online or printed using Adobe Reader. When viewed online, these files contain links and cross-references that allow you to quickly and easily locate needed information. Use the most recent version of Reader to take advantage of advanced search capabilities. For more information, see "Installing and using Adobe Reader" on page 5.

The following comprise the documentation set for your Fiery EXP4110:

- *Print Server Setup Roadmap* provides a graphical overview of minimum setup requirements to have the Fiery EXP4110 functioning on your network.
- Welcome provides an introduction to the Fiery EXP4110 and the user documentation.
- Configuration and Setup explains configuration and administration of the Fiery EXP4110
 for the supported platforms and network environments. It also includes guidelines for
 providing printing services to users.
- Printing from Windows and Printing from Mac OS describe how to install the printer
 drivers on Windows and Mac OS computers, how to establish printing connections for
 different networks, and how to begin printing from users' computers. Each document
 also describes the installation and use of print-related utilities, such as Job Monitor and
 Printer Delete Utility.
- Print Options provides information about print options for the Fiery EXP4110. This
 document describes print options and features that you access from the printer driver,
 Command WorkStation job overrides, and Hot Folder job properties.
- *Utilities* describes how to install, configure, and use the software utilities included on the User Software (Utilities) CD.
- Workflow Examples explains complicated printing scenarios and provides cross-references to relevant information in the documentation set.
- Variable Data Printing (VDP) supplements the VDP information in Workflow Examples with reference information about VDP. This document provides an overview of FreeForm and where to set FreeForm options.
- *Glossary* provides definitions for popular printing concepts, printing applications, and printing terms used in the documentation set.
- *Customer Release Notes* provide last-minute product information and workarounds for some of the problems you may encounter.

About Help



Most of the user software, utilities, and printer drivers contain Help that is accessible from Help buttons or the main toolbar menus. Help provides detailed procedures on using the application and, in some cases, provides additional detail. The documentation refers you to Help for more information as appropriate.

Installing and using Adobe Reader

For your convenience, the Adobe Reader version 6.0 for Windows and Mac OS X is included on the User Documentation CD. This version features enhanced capabilities for full rules-based search across the entire documentation set. We strongly suggest that you install this version of Reader (or a later version, if available) to take advantage of these capabilities, unless you have installed the equivalent version of Adobe Acrobat.

TO INSTALL ADOBE READER

- 1 Insert the User Documentation CD into the CD-ROM drive of your computer.
- 2 Double-click the CD icon.
- 3 Open the Adobe Reader folder.
- 4 Open the folder for your platform and double-click the installer file within (.exe for Windows, .dmg for Mac OS X).
- 5 Follow the on-screen installation instructions.

Using Adobe Reader

View or print the PDF files provided on the User Documentation CD using Adobe Reader (or Acrobat). Once you install Reader, double-click a PDF icon to open the file. Note specifically the advanced search capability of the version of Reader that is provided on this User Documentation CD. You can search for a word or phrase across all the Fiery EXP4110 documentation set by examining all the documents within a specific language folder on the User Documentation CD. For information about using this and other features of Reader, see the Help that accompanies the application.

NOTE: View the documentation from the CD or copy the language folder to your computer. If you copy the files to your computer, keep all the files in the language folder. Do not rename the files, or the cross-reference links will not work properly.

System requirements for user computers

To install the Fiery EXP4110 user software on a Windows or Mac OS computer, the computer must be equipped with a built-in or external DVD-ROM or CD-ROM drive. The following table lists the minimum system requirements.

Minimum requirements for	Windows 2000/XP/Server 2003	Mac OS
Operating system	Windows 2000 with Service Pack 4	Mac OS v9.1 to 9.2.2
	Windows XP (recommended with Service Pack 2) Windows Server 2003 Standard Edition, Enterprise Edition, or Datacenter Edition	Mac OS X v10.2.4 to 10.3.4 (PostScript printer driver only)
	(any of these must be the 32-bit version)	
Memory for printing	8MB of RAM for printing	32MB of RAM for printing
and utilities (Downloader and Job Monitor)	32MB of RAM for utilities	64MB of RAM for utilities
Networking protocol	IPX/SPX or TCP/IP	AppleTalk (EtherTalk supported)
		TCP/IP (required for Mac OS X v10.2.4 to 10.3.4)
Networking protocol for Fiery utilities	TCP/IP	TCP/IP (EtherTalk supported) (required for Mac OS X v10.2.4 to 10.3.4)
		NOTE: AppleTalk is used for Downloader.
WebTools	Java-enabled web browser:	
	• Internet Explorer v5.5 with SP2 (Windows 2000)	
	• Internet Explorer v6.0 with SP1 (Windows XP)	
	• Internet Explorer v5.1 to 5.1.7 for Mac OS (up to v5.2.3 for Mac OS X)	
	Safari v1.2 or later for Mac OS X v10.3.3 or later	
	NOTE: Microsoft releases updates to Internet Explorer. Because support cannot be guaranteed for all versions, use the versions specified for best results.	
	A monitor and video memory that supports 16-bit color at a minimum resolution of 800x600	
	A TCP/IP-enabled network and the IP address or DNS name of the Fiery EXP4110	
	Web Services enabled on the Fiery EXP4110	

Minimum requirements for	Windows 2000/XP/Server 2003	Mac OS
Command WorkStation	Windows-based computer with a 200-MHz or greater Pentium processor	Mac OS X Native v10.2.4 or later 300MHz or greater Apple Macintosh G3, G4, or G5 processor
	60MB available hard disk space for installation	80MB available hard disk space for installation 500MB is recommended for writing full previews of raster files and handling large PS or PDF files
	128MB of RAM	
	A monitor that supports 16-bit color at a minimum resolution of 1024x768 Video adapter card with 2MB of video memory TCP/IP networking protocol installed 2x CD-ROM drive	

Other network requirements

UNIX (TCP/IP) workstation	Standard TCP/IP connectivity	
	TCP/IP printing software that conforms to RFC1179 (Berkeley lpd protocol)	
IPX (Novell) network	Novell server	
	Novell NetWare software v5.x or later	
	NOTE: The iPrint feature of NetWare 6.x is not supported.	
	NDPS gateway in NetWare 5.x or later	
	Support for Ethernet SNAP, Ethernet II, Ethernet 802.3, and Ethernet 802.2 frame types	

Preparing to print

To set up your Fiery EXP4110 for printing, perform the following tasks:

Step	Task		Quick reference
1	Configure the network server	Configure network servers to specify Fiery EXP4110 print queues and Fiery EXP4110 users.	"Configuring the network server" on page 10
2	Connect the Fiery EXP4110 to a functioning network	Prepare a network node. Connect the Fiery EXP4110 to the printer and the network. If you use the Fiery Advanced Controller Interface (FACI), connect it to the Fiery EXP4110.	"Connecting the Fiery EXP4110 to a functioning network" on page 10
3	Setup the Fiery EXP4110Server SetupNetwork SetupPrinter Setup	At the Control Panel, configure at least Server Setup, Network Setup, and Printer Setup.	"Setting up the Fiery EXP4110" on page 10
4	Prepare users for printing	At each computer from which users print: • Install the appropriate printer files and connect to one or more print connections. • Install utilities and an Internet browser on computers where users will use them.	"Preparing user computers for printing" on page 12

• Verify the Fiery EXP4110 in the list of printers and print a test job.

Configuring the network server

If you require a network server, you must configure it to provide user access to the Fiery EXP4110 as a networked printer before you configure Fiery EXP4110 network settings in Setup. For more information, see *Configuration and Setup*.

Connecting the Fiery EXP4110 to a functioning network

When you add the Fiery EXP4110 to a network, it is assumed that a network administrator has already installed a network cabling system and has connected computers and servers.

TO CONNECT THE FIERY EXP4110 TO A NETWORK

- 1 Prepare a network node for the Fiery EXP4110.
- 2 Connect the Fiery EXP4110 to the printer.
- 3 Attach the network cable to the network connector of the Fiery EXP4110.

For more information, see Configuration and Setup.

4 Print a Test Page to verify that the printer is functioning normally.

For more information, see Configuration and Setup.

Setting up the Fiery EXP4110

Setup configures the Fiery EXP4110 to communicate with other devices and manage print jobs. You must perform Setup the first time you turn on the Fiery EXP4110 after new system software is loaded, or any time Server software is reinstalled.

Configure the Setup menus in the following order:

Server Setup specifies system options.

Network Setup specifies all the active network systems that transmit print jobs to the Fiery EXP4110.

Printer Setup specifies how print jobs and queues are managed.

This is the minimum configuration required to enable your Fiery EXP4110 so that users can begin printing. To configure network settings in Setup, you need a live network connection so that the Fiery EXP4110 can query the network for zones, servers, and server-based queues.

TO PREPARE FOR FIERY EXP4110 CONFIGURATION

- 1 Make sure that the network is installed and operational.
- 2 Print a printer Test Page to verify that the printer is functioning properly.
- 3 Turn off the printer and connect the interface cable from the printer to the Fiery EXP4110.
- 4 To confirm this connection, restart the Fiery EXP4110 and print a Test Page from Fiery EXP4110 Control Panel.
- 5 Shut down the Fiery EXP4110 and then the printer.
- 6 With both the printer and the Fiery EXP4110 turned off, connect the network cable to the Fiery EXP4110.
- 7 Turn on the printer and the Fiery EXP4110.

To perform Setup from the Fiery EXP4110 Control Panel, select one menu after another and enter information about your Fiery EXP4110 and your network and printing environment. In each Setup screen, the last line of the display shows the name of the current Setup menu.

TO PRINT THE CONFIGURATION PAGE FROM THE FIERY EXP4110 CONTROL PANEL

- 1 At the control panel, press the Menu button to access the Functions menu.
- 2 Press the line selection button for Print Pages.
- 3 Press the line selection button for Configuration page.

Print the Configuration page after you finish running Setup to confirm your settings.

Preparing user computers for printing

Before you can print to the Fiery EXP4110, you must install the appropriate Fiery EXP4110 software printer files from the User Software (Drivers) CD and User Software (Utilities) CD and connect users' computers to the Fiery EXP4110 over the network.

Windows computers

To set up printing for the supported Windows operating systems, do the following:

- Install the printer drivers and corresponding printer driver files.
- Configure installable print options.
- Configure the print connection between the client and the Fiery EXP4110.

For more information, see Printing from Windows.

Mac OS computers

To set up printing on a Mac OS computer, do the following:

- Install the printer driver and PPD files.
- Set up the Fiery EXP4110 in the Chooser (Mac OS X Classic) or Print Center (Mac OS X).
- Configure installable print options.

For details, see Printing from Mac OS.

Utilities provides instructions for both Windows and Mac OS computers on the following topics:

- Installing Fiery utilities
- Configuring the connection for Fiery utilities
- Using Fiery utilities
- Installing printer and screen fonts (Mac OS only)

Shutting down and rebooting the Fiery EXP4110

You may have to shut down the Fiery EXP4110 for service. When you do, network access to the printer is interrupted. Before you remove or attach any cables to the Fiery EXP4110 to perform service, shut down the Fiery EXP4110.

TO SHUT DOWN THE FIERY EXP4110

1 Make sure that the Fiery EXP4110 is not receiving, processing, or printing any files.

If the system has just finished processing, wait at least five seconds after the system reaches Idle before beginning the shutdown procedure.

NOTE: Before you remove the Fiery EXP4110 from the network, notify the network administrator.

- 2 Press the Menu button to display the Functions menu.
- 3 Use the down arrow to scroll to Shut Down.
- 4 Select Shut Down System.


Before you access internal components, make sure that all cables are disconnected from the back of the Fiery EXP4110.

TO REBOOT THE FIERY EXP4110

- 1 Make sure that the Fiery EXP4110 is not receiving, processing, or printing any files.
- 2 Press the Menu button to display the Functions menu.
- 3 Use the down arrow to scroll to Shut Down.
- 4 Select Reboot Server.

Space requirements for Fiery EXP4110 installation

Make sure that there is enough space near the printer for Fiery EXP4110 installation at your site. Allow a minimum of 8 inches (20cm) at the back and sides of the Fiery EXP4110, as shown in the following illustration.



Safety warnings



The Fiery EXP4110 Control Panel is a liquid crystal display (LCD) that is made of glass. It can break. Do not subject it to strong shocks.



If the Control Panel breaks and the liquid crystal material leaks out, do not inhale, ingest, or touch it. If the material gets on your skin or clothing, wash it off with soap and water immediately.



Do not apply excessive pressure to the panel. This changes the color of the panel.

Cleaning the Fiery EXP4110 display window

Clean the Fiery EXP4110 Control Panel with a soft cloth moistened with isopropyl alcohol or ethyl alcohol. Never use water or ketone, as these may permanently alter the display.