

EFI Fiery™ for the Xerox® EX-i C60/C70 Color Server

PostScript patch release note



Overview

This checklist will help you prepare for the installation of EN_NETBOIS.ps or DIS_NETBOIS.ps.

General Information	
○ Current Version	1.0 SP1
○ Defect ID	FIT100967781
○ Release Date	20-March-2015
○ Files included	EN_NETBOIS.ps DIS_NETBOIS.ps
○ File size	EN_NETBOIS.ps 98604bytes DIS_NETBOIS.ps 27520 bytes
○ Checksum	EN_NETBOIS.ps: 435228510 DIS_NETBOIS.ps: 1879225388

Issue(s) addressed with this release

- FIT100967781: Fiery patch to disable or enable NetBIOS PNP Password Protection

IMPORTANT

Before installing EN_NETBOIS.ps and DIS_NETBOIS.ps

- SP1 must be installed before applying either the EN_NETBOIS.ps or DIS_NETBOIS.ps patch
- EN_NETBIOS.ps: This Patch enables NetBIOS PNP Password Protection.
- DIS_NETBIOS.ps: This Patch disables the NetBIOS PNP Password Protection.

Patch installation instructions

1. Make sure that the Fiery controller has reached Idle.
2. Import either the **EN_NETBOIS.ps** or **DIS_NETBIOS.ps** using Command WorkStation to the Direct connection.
3. You must wait until the file finishes processing and Command WorkStation shows Idle.
4. From Command WorkStation, choose Server, Reboot Server.
5. Wait until the Fiery controller reaches Idle and print the configuration page.
6. Verify that the Update Info section contains the patch version **EN_NETBOIS** or **DIS_NETBIOS** depending on which patch was applied.

Disclaimer

This hardware, software/patches, or technology may contain cryptographic functions as defined in Article 8 (ix) (h) because the cryptographic capability is not user-accessible, and are designed to have only one or more of the following cryptographic functionality(ies):

1. Functionality to execute copy-protected programs
2. Functionality to access to digital contents stored on copy-protected read-only media
3. Functionality to access to encrypted and memorized digital contents on a medium that will be sold to the public with the same content
4. Functionality for copying control of copyright protected audio/video data
5. Functionality to encrypt and/or decrypt to protect libraries, design attributes, or associated data for the design of semiconductor devices or integrated circuits