

EFI Fiery™ for the Xerox® EX C60/C70 Color Server

EXE patch release note



Overview

This checklist will help you prepare for the installation of **FIT101500097.exe**.

General Information	
○ Current Version	2.0
○ Defect ID	FIT101500097
○ Release Date	27-September-2016
○ Files included	FIT101500097.exe
○ File size	5278368 bytes
○ Checksum	4028667761

Issue(s) addressed with this release

- **FIT101500097: Patch to address Fiery Exit and Image Viewer Curve options missing issues.**
- FIT101500097: On Russian locale, Fiery Exit seen after doing backup/restore from Xerox EX-C60-C70 1.0 to Xerox EX-C60-C70 2.0 on same hardware.
- FIT101525903 : Options under Image Viewer Curves drop down under Color tab of Job Properties goes black after restoring Xerox EX-C60-C70 1.0 backup file on Xerox EX-C60-C70 2.0

Steps to reproduce the issue(s)

- **FIT101500097 : On Russian locale, Fiery Exit seen after doing backup/restore from Xerox EX-C60-C70 1.0 to Xerox EX-C60-C70 2.0 same hardware**
 1. Install the build on Russian locale on Xerox EX-C60-C70 1.0 and do a system update till SP2
 2. Do some changes on the server and take a backup of Xerox EX-C60-C70 1.0
 3. On the same hardware install Russian + SP1 (successor) on Xerox EX-C60-C70 2.0
 4. Restore using backup file taken in step1.

Result: While restore operation is in progress, server exit is observed.

- **FIT101525903 : Options under Image Viewer Curves drop down under Color tab of JP goes black after restoring Xerox EX-C60-C70 1.0 backup file on Xerox EX-C60-C70 2.0**
 1. Connect Command WorkStation and import a job to Hold queue.
 2. Launch Job Properties for the job and go to Color Tab
 3. Check the Image Viewer Curves drop down and check the options available and close Job Properties.
 4. Go to Server Menu and select Backup/Restore
 5. Select Restore option and select the previously Backed Up file of Xerox EX-C60-C70 1.0.
 6. After the restore is completed reboot the server.

Disclaimer

This hardware, software/patches, or technology may contain cryptographic functions as defined in Article 8 (ix) (h) because the cryptographic capability is not user-accessible, and are designed to have only one or more of the following cryptographic functionality(ies):

1. Functionality to execute copy-protected programs
2. Functionality to access to digital contents stored on copy-protected read-only media
3. Functionality to access to encrypted and memorized digital contents on a medium that will be sold to the public with the same content
4. Functionality for copying control of copyright protected audio/video data
5. Functionality to encrypt and/or decrypt to protect libraries, design attributes, or associated data for the design of semiconductor devices or integrated circuits

EFI Fiery™ for the Xerox® EX C60/C70 Color Server

EXE patch release note



7. Once the Server comes back to idle launch the Job Properties of the previously held job and repeat Step 2 and 3.

Result: The Image Viewer Curve drop down does not show any values/options.

IMPORTANT

Before installing FIT101500097.exe

- 1 Known issues listed below, read before installing **FIT101500097.exe** patch:
 - None.
- 2 The following prerequisite(s) must be installed in the order specified before applying the **FIT101500097.exe** patch:
 - SP1
- 3 Do NOT install any of the following patch(es) after installing the **FIT101500097.exe** patch. If you must install any of the patch(es) below, do so before installing the **FIT101500097.exe** patch:
 - None.
- 4 This patch is not exclusive, it can be installed along with other patches concurrently, and one server Reboot is sufficient for all patches to take effect on the system.

Patch installation instructions

- 1 Make sure that the Fiery printer controller reaches Idle.
- 2 Execute **FIT101500097.exe** and follow the instructions in the Fiery Patch Downloader.
- 3 Notes about the Fiery Patch Downloader
 - a. Logon must be admin. This is fixed and cannot be modified.
 - b. Password is the Fiery administrator login password.
 - c. Hostname can be the IP address or the Fiery server name.
- 4 After the patch is downloaded, When prompted by the Fiery Patch Downloader, choose Reboot. (*If you choose to Restart later, make sure you manually reboot the server for the changes to take effect*)
- 5 Wait until the Fiery controller reaches Idle and print the Configuration page.
- 6 Verify that the **System Updates Log** section contains the patch number **FIT101500097**.

Disclaimer

This hardware, software/patches, or technology may contain cryptographic functions as defined in Article 8 (ix) (h) because the cryptographic capability is not user-accessible, and are designed to have only one or more of the following cryptographic functionality(ies):

1. Functionality to execute copy-protected programs
2. Functionality to access to digital contents stored on copy-protected read-only media
3. Functionality to access to encrypted and memorized digital contents on a medium that will be sold to the public with the same content
4. Functionality for copying control of copyright protected audio/video data
5. Functionality to encrypt and/or decrypt to protect libraries, design attributes, or associated data for the design of semiconductor devices or integrated circuits