

EFI Fiery™ for the Xerox® EX C60/C70 Color Server

EXE patch release note



Overview

This checklist will help you prepare for the installation of **FIT101695387.exe**.

General Information	
○ Current Version	2.0_SP1
○ Defect ID	FIT101695387
○ Release Date	27-April-2017
○ Files included	FIT101695387.exe
○ File size	307710896 bytes
○ Checksum	812464501

Issue(s) addressed with this release

- FIT101695387: Fiery Patch to support Advanced Punch Pro Finisher.
- FIT101647382: A5 LEF/SEF offset and A5 LEF punch feature for BR Finisher.

IMPORTANT

Before installing FIT101695387.exe

- 1 Known issues listed below, read before installing **FIT101695387.exe** patch:
 - This patch obsoletes the patch: **FIT101613722**, **FIT101606523**
- 2 The following prerequisite(s) must be installed in the order specified before applying the **FIT101695387.exe** patch:
 - SP1
 - FIT101500097
- 3 Do NOT install any of the following patch(es) after installing the **FIT101695387.exe** patch. If you must install any of the patch(es) below, do so before installing the **FIT101695387.exe** patch:
 - None.
- 4 This patch is exclusive, it must be installed by itself, and the server must be rebooted or restarted once. After that, other patches can be applied to the server.

Patch installation instructions

- 1 Make sure that the Fiery printer controller reaches Idle.
- 2 Execute **FIT101695387.exe** and follow the instructions in the Fiery Patch Downloader.
- 3 Notes about the Fiery Patch Downloader
 - a. Logon must be admin. This is fixed and cannot be modified.

Disclaimer

This hardware, software/patches, or technology may contain cryptographic functions as defined in Article 8 (ix) (h) because the cryptographic capability is not user-accessible, and are designed to have only one or more of the following cryptographic functionality(ies):

1. Functionality to execute copy-protected programs
2. Functionality to access to digital contents stored on copy-protected read-only media
3. Functionality to access to encrypted and memorized digital contents on a medium that will be sold to the public with the same content
4. Functionality for copying control of copyright protected audio/video data
5. Functionality to encrypt and/or decrypt to protect libraries, design attributes, or associated data for the design of semiconductor devices or integrated circuits

EFI Fiery™ for the Xerox® EX C60/C70 Color Server

EXE patch release note



- b. Password is the Fiery administrator login password.
 - c. Hostname can be the IP address or the Fiery server name.
- 4 After the patch is downloaded, when prompted by the Fiery Patch Downloader, choose Reboot. (*If you choose to Restart later, make sure you manually reboot the server for the changes to take effect*)
- 5 Wait until the Fiery controller reaches Idle and print the Configuration page.
- 6 Verify that the **System Updates Log** section contains the patch number **FIT101695387**.

Disclaimer

This hardware, software/patches, or technology may contain cryptographic functions as defined in Article 8 (ix) (h) because the cryptographic capability is not user-accessible, and are designed to have only one or more of the following cryptographic functionality(ies):

1. Functionality to execute copy-protected programs
2. Functionality to access to digital contents stored on copy-protected read-only media
3. Functionality to access to encrypted and memorized digital contents on a medium that will be sold to the public with the same content
4. Functionality for copying control of copyright protected audio/video data
5. Functionality to encrypt and/or decrypt to protect libraries, design attributes, or associated data for the design of semiconductor devices or integrated circuits