

The Document Company

XEROX

DC220/230ST Windows NT® 4.0 NetBIOS/NetBEUI Quick Install

Installation Requirements:

If this is a Token Ring installation, the Token Ring card must be installed by your Xerox service representative and configured before performing this procedure. Refer to the Token Ring Quick Install card.

Before Installation:

Record the following information for use during setup at the DC220/230:

Host Name: _____

Printer Name: _____

Workgroup: _____

1. Connect the DC220/230 to your network outlet or cable.
2. Enter System Administration Setups:
 - a) Press the **[Access]** button on the Control Panel.

- b) Enter the System Administrator password by typing **#22222** (**# key and 22222**) on the keypad and pressing **[Enter]** on the screen.
Note: #22222 is the factory default password and may be changed by your Xerox service representative to suit your needs.
3. Access the Setup screens:
 - a) On the screen display, press **[Print Setups]**.
 - b) Press **[Network Setups]**.
 - c) Press **[NetBIOS/NetBEUI]**.
4. Enable NetBIOS/NetBEUI:
 - a) Press **[Enablement]**.
 - b) Press **[Enabled]**.

5. Select the appropriate interface:
 - a) Press **[Interface]**.
 - b) On the right half of the screen, select **[Ethernet]** or **[Token Ring]** as the appropriate interface for your network.
Note: Token Ring will not be available as a selection unless it has been installed and configured.
6. Enter the Host Name:
 - a) Press **[Host Name]**, then press **[Edit]** and use the keyboard on the screen to enter the Host Name for your network (14 characters or less).
 - b) Press **[Save]**.
7. Enter the Printer Name:
 - a) Press **[Printer Name]**, then press **[Edit]** and use the keyboard on the screen to enter the Printer Name for your network (15 characters or less).
 - b) Press **[Save]**.

The Document Company

XEROX

DC220/230ST Windows NT® 4.0 NetBIOS/NetBEUI Quick Install

8. Enter the Workgroup name:
 - a) Press **[Workgroup]**, then press **[Edit]** and use the keyboard on the screen to enter the Workgroup Name.
 - b) Press **[Save]**.
9. Press **[Save]**.
10. Press **[Exit]**.
11. The DC220/230 will reboot and print a configuration sheet in approximately 3 minutes.

12. Check the settings on the configuration sheet against those that were entered.
13. At the client, install print drivers and map the printer in the usual manner. Refer to the CentreWare® manual, *Getting Started with Print and Fax Services* for additional information.

Additional information on this installation procedure can be found in the *DC220/230 System Administration Guide*.