

The Document Company

XEROX

DC220/230ST Token Ring® Quick Install

Installation Requirements:

The Token Ring card must be inserted **face down** to obtain connectivity.

1. Perform the following procedure if Token Ring will be selected as the Interface for the network:
 - a) Press the **[Access]** button on the Control Panel.
 - b) Enter the System Administrator password by typing **#22222** (**# key and 22222**) on the keypad and pressing **[Enter]** on the screen.

Note:#22222 is the factory default password and may be changed by your Xerox service representative to suit your needs.
 - c) On the screen display, press **[Print Setups]**.
 - d) Press **[Port Setups]**.
 - e) Press **[Token Ring]**.

- f) Press **[Enablement]**.
 - g) Press **[Enabled]**.
 - h) Press **[Source Routing]** and select either **[All]**, **[Single]**, or **[None]**.
 - i) Press **[Speed]** and select either **[Auto]**, **[4 Mbps]** or **[16 Mbps]**.
 - j) Press **[Save]**.
 - k) Press **[Close]**. The DC220/230 will reboot and print a configuration sheet in approximately 3 minutes.
2. Check the settings on the configuration sheet against those that were entered.
3. Refer to the Quick Install card for your environment and perform the network installation at the DC220/230.

Additional information on Token Ring installation can be found in the *DC220/230 System Administration Guide*.