### Recommended Xerox Materials for DocuColor 12 LP/CP (USA and Canada)

### For use in the US and Canada

Revision 2.6, Publish Date: Sept. 27th, 2002

Last Revision 2.5 was published on July 3rd, 2002

For the most recent version of this quarterly published document, visit www.xdss.com, select "Free Downloads", then "Color".

### **Important Notes:**

All media is listed by product, machine run mode, weight (standard gsm), re-order number, size, and tray runability. The additional information column is for hints and tips on how to run certain media applications.

Media recommendations made in this publication are based on qualification tests\* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.


- \* Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.
- \*Machine reliability specifications may be affected by increased usage of Heavy Weight mode and Extra Heavy Weight mode. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox Sales or Service representative can advise you on using Heavy Weight mode, Extra Heavy Weight mode or special application media types for long duration copy/print runs.


For specifications and a description of the various media types discussed in this publication, please refer to the Color Material Usage Guide (reorder number 701P34322) that comes with your equipment.


© 2001 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

Tray 1: Normal Mode ( 64	-105 gsm) 🔲								A=	Auto [	Duple	(		
Trays 2,3,& 4: Normal (64	- · — ·		-		DC12 LP/C	P:			M=N	/lanual	duple	ex		Tray 5 Tip for Extra Heavyweight Paper: Select Short Edge Feed (SEF), if media jams on Long Edge Feed (LEF).
Tray 5: Normal (64-105gs Extra Heavyweight (164-		106-163gsm) parency						PC		Simple st Cons			•	reed (SEI ), il lifedia jams on Long Luge reed (LEI ).
Tray 6 (HCF): Normal (64-		eight (106-163	gsm) $\square$					ECF	=Elen	nental (	Chlori	ne Fre	е	
Media	Mode	Weight	Re-Order #	Туре	Size	Т			Trays			HCF		Additional Information
			110 01001 11	71		<sup>⊥</sup>  -	1	2	3	4	5	6		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Xerox Premium		75 gsm /	3R721		8.5 x 11	<b>→</b>	Α	Α	Α	Α	M	Α		
Multipurpose 4024	Normal	20lb	3R727 3R729		8.5 x 14 11 x 17			A	A	A	M		<b>→</b>	Black/ White copies only.
				] 1		ĭ ►[								
		90 gsm /	3R11380 3R11381(3 Hole)		8.5 x 11 8.5 x 11		A	A	A	A	M	A		
	-	24lb	3R11382		8.5 x 14		Α	A	A	A	M	А	-	
	Normal		3R11383		17 x 11	<b>—</b>		Α	A	Α	M			
		105gsm/	3R11385		8.5 x 11		Α	Α	Α	Α	М	Α		
Vanna D'altal Oalan		28lb	3R11386		17 x 11			A	A	A	M		<b>→</b>	
Xerox Digital Color Xpressions +			3R11387	]	8.5 x 11	<b>├</b>		S	S	S	М	М		
-	Heavyweight	120gsm/	3R11388		17 x 11	-		S	S	S	M		<b>→</b>	Trays 2,3, & 4: Enable Heavyweight Mode. Tray 5: Side 2- Heavyweight Mode.
		32lb	3R11389		18 x 12	<b> </b>		S	S	S	M			neavyweight mode.
				1		т ъг								
	- Heavyweight	163gsm /	3R11390 3R11391		8.5 x 11 17 x 11						M			Tray 5: Side 2- Heavyweight Mode.
	Heavyweight	60lb	3R11384		17 x 11						M			11ay 3. Side 2- Heavy weight Mode.
			3R5529	1 ]	8.5 x 11	⊥ · ∟ ∐—▶[	Α	Α	Α	Α	M	Α		
_	Normal	105gsm/	3R5530		17 x 11			Ā	A	A	M	Α	<b>→</b>	PCW=30%
		28lb	3R5531		18 x 12	<b>-</b>		S	S	S	М			
		400	3R6385	-	8.5 x 11	<b>I</b> →Γ					М			
	Heavyweight	163gsm/ 60lb	3R6386		17 x 11	ightharpoons					M		-	Tray 5: Side 2- Heavyweight Mode. PCW=30%
Xerox Digital Color Xpressions 98' (Ultra		OOID	3R6387		18 x 12	<b> -&gt;</b>					M			1 3 11 - 3 17
White)		175gsm/	3R5533		8.5 x 11						М			
		65lb	3R5534		17 x 11						M		<b>→</b>	
_	Extra Heavyweight		3R5535		18 x 12						M			Tray 5:Side 2-Extra Heavyweight Mode.
	, ,	215gsm/	3R5537		8.5 x 11	<b>-&gt;</b>					M		_	PCW=30%
		80lb	3R5538		17 x 11						M		-	
			3R5539		18 x 12						M			
			3R11244	White	8.5 x 11		Α	Α	Α	Α			<b>→</b>	
			3R11248		17 x 11			Α	Α	Α				
			3R11245	Gold	8.5 x 11		Α	Α	Α	Α			<b>→</b>	Due to the unique curfees nottorns in Development names this
Xerox Digital Color	Normal	90gsm/	3R11249		17 x 11			Α	Α	Α				Due to the unique surface patterns in Parchment paper, this product will exhibit image mottle as a design feature.
Parchment		24lb	3R11246	Orchio	8.5 x 11	<b> </b>	Α	Α	Α	Α			<b>→</b>	PCW=30%
			3R11250		17 x 11	<b> </b>		Α	Α	Α			•	
			3R11247	Pewte	8.5 x 11	<b> </b>	Α	Α	Α	Α		_	_	
			3R11251	. CWIC	17 x 11			Α	Α	Α				







Tray 1: Normal Mode ( 64	·105 gsm) 🔲							Δ-	Auto [	Dunla	,		
Trays 2,3,& 4: Normal (64	-105gsm)   Heavywe	eight (106-128gsm)	DO	C12 LP/ C	P:				/lanual	•			Tray 5 Tip for Extra Heavyweight Paper: Select Short Edge
Tray 5: Normal (64-105gs	m) Heavyweight (	106-163gsm)							Simple		-		Feed (SEF), if media jams on Long Edge Feed (LEF).
Extra Heavyweight (164-2	250gsm) Trans	parency							st Cons				
Tray 6 (HCF): Normal (64-	105gsm) 🔲 Heavyw	eight (106-163gsm)	_				ECF	-=Eleli	ientai	Chion	ne Fre	ee	
Media	Mode	Weight Re-Order #	Туре	Size	Ī			Trays			HCF	Ī	Additional Information
						1	2	3	4	5	6		
Xerox Digital Color Trifold Brochures	Heavyweight Mode	120gsm / 3R12310		8.5 X 11	<b> </b>					M		-	Short Edge Feed in the Bypass Tray.
Xerox Digital Color Super Gloss Greeting Card (C1S)	Extra Heavyweight	10pt./ 210gsm 3R6340		8.5 x 11						М		<b>→</b>	Side 2- Extra Heavyweight Mode. Duplex text or light area coverage/ Print on uncoated side first.
Xerox Index Stock	Heavyweight	163gsm/ 3R3004 90lb 3R5102		8.5 x 11 11 x 17						M		<b> </b>	Side 2- Heavyweight Mode. Black/ White Copies Only.
Xerox One- Step	Heavyweight	3R5811		8.5 x 11						S			
Transfer Paper	Tleavyweight	3R5812		11 x 17	<b>[→</b> [					S			
		3R5770	1-up	8.5 x 11	<b> →</b> [		S	S	S			ĪΙ	
Xerox Digital Color		3R5771	4-up	8.5 x 11			S	S	S				Trave 2.2. 8.4 must be set for begunnight made Load
Xpressions Gloss	Heavyweight	3R6324	10-up	8.5 x 11	<b>-</b>		S	S	S				Trays 2,3, & 4 must be set for heavyweight mode. Load labels, image side face down in the tray, long edge feed
Coated Labels		3R6325	30-up	8.5 x 11			S	S	S			-	(LEF).
		3R6320	VCR	8.5 x 11			S	S	S				
		3R6322	CDR	8.5 x 11			S	S	S				
		3R5772	1-up	8.5 x 11	<b> -&gt;</b> [		S	S	S				
Xerox Digital Color		3R5773	4-up	8.5 x 11	<b>]→</b> [		S	S	S				Trans 0.2 0.4 months and for borrowsish to and in and and
Xpressions Matte	Heavyweight	3R6332	10-up	8.5 x 11	<b>→</b>		S	S	S				Trays 2,3, & 4 must be set for heavyweight mode in order to run labels. Load labels, image side face down in the tray,
Coated Labels	- ricavyweight	3R6333	30-up	8.5 x 11	<b> →</b> _		S	S	S			_	long edge feed (LEF). ECF
		3R6328	VCR	8.5 x 11	<b>├</b>		S	S	S				
		3R6330	CDR	8.5 x 11	<b> →</b> _		S	S	S				
Xerox Bright White	Heavyweight	3R12177	1-up	8.5 x 11			S	S	s				Trays 2,3, & 4 must be set for heavyweight mode in order to run labels. Load labels, image side face down in the tray,
Labels		3R12179	30-up	8.5 x 11			S	S	S				long edge feed (LEF).
		3R4476	1-up	8.5 x 11	<b> -</b>		S	S	S				
Vanau Hinh Char		3R4475	8-up	8.5 x 11	<b>├</b>		S	S	S				Trays 2,3, & 4 must be set for heavyweight mode in order to
Xerox High Speed Labels	Heavyweight	3R5719	14-up	8.5 x 11	┝		S	S	S			-	run labels. Load labels, image side face down in the tray,
Labeis		3R4474	24-up	8.5 x 11	<b> →</b>		S	S	S			1	long edge feed (LEF). Black &White Copies Only.
		3R3139	33-up	8.5 x 11	<b>]→</b>		S	S	S			]	
		3R6339	Clear	8.5 x 11	⊢⊸「					S	1	Ī	
Xerox Digital Color	Heavyweight	3R12059	Opaque	8.5 x 11						s			Color Copies Only.
Window Decals	, , , ,	3R12315	Opaque	11 x 17						S			

Tray 1: Normal Mode ( 6	4-1	05 gsm) 🔲										A=	- Auto	Duple	(		
Trays 2,3,& 4: Normal (6			_		m)	j	D	C12 LP/ C	P:				Manua	•			Tray 5 Tip for Extra Heavyweight Paper: Select Short Edge Feed (SEF), if media jams on Long Edge Feed (LEF).
Tray 5: Normal (64-105g Extra Heavyweight (164											PC		Simple st Con			е	reed (SEI ), il liledia jams on Long Luge reed (LEI ).
Tray 6 (HCF): Normal (6					sm)	1							nental				
Media		Mode	Ī	Weight	Re-Order #	T	уре	Size	7 [			Trays	,		HCF	Ī	Additional Information
			L						_	1	2	3	4	5	6		
Xerox Digital Color Transparency		Transparency Mode -			3R5765			8.5 x 11						s		<b>-</b>	
Xerox Removable					3R12277			8.5 x 11	<b>-</b>					S			
Stripe Transparency		Transparency Mode -			3R5821			11 x 17	-					s			Transparency 3R12277 replaced 3R3108
Xerox Digital Color		Extra Heavyweight		245 gsm	3R12155			8.5 x 11	<b> </b>					s		_	For use ONLY with Pixography system. **See Appendix A for
Photo Glossy Paper				240 go	3R12156			17 x 11	<b> -</b>					s			detailed instructions. PCW=10%
				-	3R12266		nmercial white	18 x 12	<b> </b>					s		<b>→</b>	For one Only with the Metabories Professional Common and
Xerox Imation Matchprint™ Color Laser Proofing Paper		Extra Heavyweight	_	245 gsm -	3R12267	sup	er white	18 x 12	<b> </b>					s		<b>-</b>	For use Only with the Matchprint Professional Server, and the Xerox DC12 Color Proofing Solution. **See Appendix B for a instruction sheet. Short edge feed (SEF) in bypass tray. Color Copies Only.
				_	3R12271		olication white	18 x 12						s		<b>-</b>	
Xerox Digital Color High Gloss Folder (C2S)		Extra Heavyweight	_	176 gsm -	- 3R5570			9.25 x 11.75	<b> </b>					s		<b>→</b>	For Fiery, select Custom Page Size Definition for printing.
Xerox Digital Color High Capacity Folder (C1S)		Extra Heavyweight	_	10pt. / 210gsm	- 3R12313			9.5 x 11.75	<b> </b>					s		<b>→</b>	For Fiery, select Custom Page Size Definition for printing.
Xerox Digital Metallic					3R12311	S	Silver	8.5 x 11								Ī	
Covers		Extra Heavyweight	7	213 gsm	3R12312	(	Gold	8.5 x 11						S			
			_									•	•				

# PHOTO GLOSSY PAPER DIGITAL COLOR

## STEPS FOR SUCCESS

- Insert paper from Paper Tray 5 only and the side facing up will be imaged
- When duplex printing:
- image low gloss side of sheet first.
- the lead edge/first edge out should be the lead edge/first edge fed from the Paper Tray 5 on the second pass.
- the side imaged first should be facing down when feeding through the *Paper Tray 5* on the second pass.

### TIPS

- Store product *flat* at all times, preferably with glossy side up.
- Place unused product in original box and store within the re-sealable plastic package between uses.
- Handle sheets by the edges to avoid fingerprints.
- Prior to use, condition paper to room temperature.

### COMPATIBILITY

	DC12**	Machine
(commonly known as Bypass Tray)	Paper Tray 5	Trays
Heavyweight	Extra	Media Type

\*\*NOTE: Premium paper specifically designed for use ONLY with the Xerox Pixography™ system.