

# Recommended Materials for DocuColor 5750, Office 6 (USA and Canada)

Revision 1.6, Publish Date: July 20, 2000

Last Revision 1.5 was published on March 24, 2000

Any additions to this document since last publication are indicated in blue

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

## Important Note:

Media recommendations made in this publication are based on qualification tests\* conducted using standard test images with moderate to heavy image area coverage. Test duration for each product/media type is based on the suggested machine monthly copy/print volume. Test machines are maintained within specifications defined by user documentation.

\* Testing Environment temperature range of 60-75 deg. F, Relative Humidity range 20-40%.

In the enclosed Recommended Materials List, green shaded areas marked with an "x" indicate approved product/media type configurations. Although these configurations are recommended, reliability is based on your operating environment and application mix.

Machine reliability specifications may be affected by increased usage of Heavy Weight Paper mode and other special paper modes. In addition, variances in machine reliability may occur due to extended use of some media types. Your Xerox Sales or Service representative can advise you on using Heavy Weight Paper and other special paper modes or special application media types for long duration copy/print runs.

For specifications and a description of the various media types discussed in this publication, please refer to the Color Material Usage Guide (reorder number 701P31305) that comes with your equipment.

© 2000 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)										
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *									
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm							
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass			
<b>Recommended Xerox Brand Materials List</b>																		
<b>Business Papers (bond, xerographic and laser grades)</b>																		
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White) <b>3-Hole</b>	3R5464			24	90	x	x	x	x								x	
	3R5466 (8.5x14)			24	90	x	x	x	x								x	
		3R5465 *		24	90	x	x	x	x								x	
<b>Digital Color Allure</b>	3R5467			24	90	x	x	x	x								x	
	3R11120			24	90	x	x	x	x								x	
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White)	3R11121			24	90	x	x	x	x								x	
	3R5468			28	105	x	x	x	x								x	
<b>Digital Color Allure</b>	3R5469			28	105	x	x	x	x								x	
	3R11122			28	105	x	x	x	x								x	
<b>Digital Color Xpressions 98</b> (Color Xpressions Ultra White)	3R11123			28	105	x	x	x	x								x	
	3R5529			28	105	x	x	x	x								x	
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White)	3R5530			28	105	x	x	x	x								x	
		3R5531		28	105	x	x		x								x	
	3R5470			32	120	x	x				x						x	
	3R5471			32	120	x	x				x						x	
		3R5472		32	120	x	x				x						x	
<b>Book Papers (premium text, coated &amp; uncoated book papers)</b>																		
<b>premium text/uncoated papers</b> --Same paper fits both Business Papers and Book Papers categories																		
<b>offset weight</b>																		
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White) <b>3-Hole</b>	3R5464			60 lb offset = 24 lb Bond Paper = 90 gsm		x	x	x	x								x	
		3R5465				x	x	x	x									x
	3R5467					x	x	x	x									x
<b>Digital Color Allure</b>	3R11120			60 lb offset = 24 lb Bond Paper = 90 gsm		x	x	x	x								x	
		3R11121				x	x	x	x									x
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White)	3R5468			70 lb offset = 28 lb Bond Paper = 105 gsm		x	x	x	x								x	
		3R5469				x	x	x	x									x

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)								
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *							
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm					
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass	
<b>Digital Color Allure</b>	3R11122			70 lb offset = 28 lb Bond Paper = 105 gsm	x	x	x	x							x	
		3R11123			x	x	x	x								x
<b>Digital Color Xpressions 98</b> (Color Xpressions Ultra White)	3R5529			70 lb offset = 28 lb Bond Paper = 105 gsm	x	x	x	x							x	
		3R5530			x	x	x	x								x
			3R5531		x	x		x								x
<b>Digital Color Xpressions 94</b> (Color Xpressions Bright White)	3R5470			80 lb offset = 32 lb Bond Paper = 120 gsm	x	x				x					x	
		3R5471			x	x				x						x
			3R5472		x	x				x						x
<b>Coated Text</b>				<b>offset weight</b>												
<b>Digital Color Xpressions Gloss Coated Text</b>	3R5574			80	120	x	x				x					
		3R5575		80	120	x	x				x					
			3R5576	80	120	x	x				x					
<b>Digital Color Xpressions Matte Coated Text</b>	3R6341			80	120	x	x				x					
		3R6342		80	120	x	x				x					
			3R6343	80	120	x	x				x					
<b>Index Papers</b>				<b>Index weight</b>												
<b>90 lb Xerox Index Stock</b>	3R3004			90	163	x					x				x	
		3R5102		90	163	x					x				x	
<b>Covers</b>				<b>Cover weight</b>												
<b>Uncoated Cover</b>				<b>Cover weight</b>												
<b>Digital Color Xpressions 98</b> (Color Xpressions Ultra White)	3R6385			60	163	x	x				x				x	
		3R6386		60	163	x	x				x				x	
			3R6387	60	163	x	x				x				x	
<b>Digital Color Allure</b>	3R11124			60	163	x	x				x				x	
		3R11125		60	163	x	x				x				x	
<b>Digital Color Xpressions 98</b> (Color Xpressions Ultra White)	3R5533			65	175	x	x					x			x	
		3R5534		65	175	x	x					x			x	
			3R5535	65	175	x	x					x			x	
<b>Digital Color Xpressions 98</b> (Color Xpressions Ultra White)	3R5537			80	215	x	x					x			x	
		3R5538		80	215	x	x					x			x	
			3R5539	80	215	x	x					x			x	

Recommended Materials for 5750/Office 6

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)								
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *							
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm					
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass	
<b>Coated Two Side Cover (C2S)</b>																
<b>Cover weight</b>																
Digital Color Xpressions Gloss Coated Cover	3R5571			80	215	x	x					x			x	
		3R5572		80	215	x	x					x			x	
			3R5573	80	215	x	x					x			x	
Digital Color Xpressions Matte Coated Cover	3R6344			80	215	x	x					x			x	
		3R6345		80	215	x	x					x			x	
			3R6346	80	215	x	x					x			x	
<b>Coated Cover (one side, C1S)</b>																
Digital Color Super Gloss (Super Gloss)	3R6290			8 pt	160	x	x				x				x	limited duplex with text or low toner coverage on uncoated side first
		3R6291		8 pt	160	x	x				x				x	
			3R6292	8 pt	160	x	x				x				x	
Digital Color Super Gloss (Super Gloss)	3R6293			10 pt	210	x	x					x			x	
		3R6294		10 pt	210	x	x					x			x	
			3R6295	10 pt	210	x	x					x			x	
Digital Colour Coated Cover (C1S) -- <a href="#">available in Xerox Canada only</a>	3R13031			8 pt	160	x	x				x				x	limited duplex with text or low toner coverage on uncoated side first
		3R13032		8 pt	160	x	x				x				x	
			3R13033	8 pt	160	x	x				x				x	
Digital Colour Coated Cover (C1S) -- <a href="#">available in Xerox Canada only</a>	3R13034			10pt	210	x	x					x			x	
		3R13035		10pt	210	x	x					x			x	
			3R13036	10pt	210	x	x					x			x	
<b>Transparencies</b>																
Color Xpressions Digital Color Transparency	3R5765					x	x						x			
Removable Stripe Transparency	3R3108					x							x			
		3R5821				x	x						x			

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)								
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *							
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm					
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass	
<b>Pressure Sensitive Labels</b>																
<b>Bright White Labels</b>	3R12177			1-UP		x	x							x		
	3R12179			30-UP		x	x							x		
<b>Digital Color Xpressions Gloss Coated Labels</b>	3R5770			1-UP		x	x							x		
	3R5771			4-UP		x	x							x		
	3R6324			10-UP		x	x							x		
	3R6325			30-UP		x	x							x		
	3R6320			VCR		x	x							x		
	3R6322			CD-ROM		x	x							x		
	3R6323			Diskette		x	x							x		
<b>Digital Color Xpressions Matte Coated Labels</b>	3R5772			1-UP		x	x							x		
	3R5773			4-UP		x	x							x		
	3R6332			10-UP		x	x							x		
	3R6333			30-UP		x	x							x		
	3R6328			VCR		x	x							x		
	3R6330			CD-ROM		x	x							x		
	3R6331			Diskette		x	x							x		
<b>Xerox Low Speed Labels</b>	3R4473			1-UP		x								x		
	3R4472			8-UP		x								x		
	3R4471			24-UP		x								x		
	3R4469			33-UP		x								x		
	3R6160			10-UP		x								x		
	3R6159			20-UP		x								x		
	3R5113			30-UP		x								x		
	3R5722			Diskette		x								x		

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)								
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *							
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm					
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass	
Xerox High Speed Labels	3R4476			1-UP		x							x			
	3R3146			6-UP		x							x			
	3R4475			8-UP		x							x			
	3R5719			14-UP		x							x			
	3R4474			24-UP		x							x			
	3R3139			33-UP		x							x			
Xerox High Speed Labels (Clear)	3R5139			33-UP		x							x			
Special Stocks																
Xerox One Step T-Shirt Transfer Paper	3R5811					x	x		One-Step Transfer Paper mode							
		3R5812				x	x		One-Step Transfer Paper mode							
Gloss Coated Presentation Folders	3R5570	9 x 11"		8 pt	200	x	x				x			x	x	
Xerox DocuPac Folders	3R4885	9 x 11"				x				x				x	x	
Glossy Greeting Card (coated one side, C1S)	3R6337			8 pt	160	x	x			short edge feed				short edge feed		
	3R6340			10 pt	210						short edge feed			short edge feed		
Glossy Trifold Brochure (coated one side, C1S)	3R6342			8 pt	160	x	x			short edge feed				short edge feed		
Xerox DocuCard	3R6336			1-UP	163											
Business Card	x			10-UP	215	x	x				x				x	

For the most recent version of this quarterly published document, visit [www.xdss.com](http://www.xdss.com), select "Product Literature Download", "Color"

	Size (US & Canada)			Weight (lb)	Weight (g/m <sup>2</sup> )	Output Selection		5750 (Empress/Office6)									
	8.5x11"	17x11", grain short	18x12", grain short			Black only	Full Color	Internal trays	bypass tray 64 - 203 gsm *								
Weight range specification	→							64 - 105 gsm	64-105 gsm	106-163 gsm	164-203 gsm						
Media selection	→							plain paper mode	plain paper mode	heavy weight/thick paper mode	extra heavy weight mode /thick2	trans- parency mode	label mode	coated paper	manual duplex from bypass		
<b>Recommended Non-Xerox Brand Papers</b>																	
<b>Business Papers (bond, xerographic and laser grades)</b>																	
Weyehaeuser First Choice	x			24	90	x	x	x	x								x
Hammermill Laser Print	x			24	90	x	x	x	x								x
		x		24	90	x	x	x	x								x
Georgia Pacific Microprint Laser 1000	x			24	90	x	x	x	x								x
		x		24	90	x	x	x	x								x
Hammermill Color Copy Photo White	x			28	105	x	x	x	x								x
		x		28	105	x	x	x	x								x
Georgia Pacific Microprint Laser 1000	x			28	105	x	x	x	x								x
		x		28	105	x	x	x	x								x
Georgia Pacific Microprint Color Copy Paper	x			28	105	x	x	x	x								x
	x			32	120	x	x										x
Hammermill Laser Print		x		32	120	x	x										x
<b>Covers--Uncoated Cover</b>																	
<b>Cover weight</b>																	
Color Copy Cover (Hammermill )	x			60	160	x	x										x
		x		60	160	x	x										x

**WARRANTY DISCLAIMER**

Xerox makes no guarantees or warranties, either express or implied, concerning the performance, use or replacement of non-Xerox branded media or throughput products. Customers should inquire directly of their paper distributor or manufacturer for any guarantees they may offer. When purchasing a particular media product for the first time, customers are advised to purchase small quantities to insure that their expectations are met.

The quality of Xerox supplies is consistent from ream to ream, carton to carton, and it is backed by a Xerox 100% guarantee. The quality of non-Xerox branded paper may vary from ream to ream or carton to carton, so for optimum performance on Xerox color equipment, use only the best--Xerox Supplies.

© 2000 Xerox Corporation. All rights reserved.

Xerox®, The Document Company®, the stylized X®, and all Xerox product names and product names and product numbers mentioned in this publication are trademarks of Xerox Corporation. Other company trademarks are also acknowledged.

# ***COLOR LASER BRIGHT WHITE LABELS***

## ***STEPS FOR SUCCESS***

**5750 / 5765 / 5790 / 5799**

1. Load sheets in the BYPASS Tray \*\*.
2. Select ***Label/Heavy Weight*** Mode.
3. Remove sheets from the output device after 50 sheets. Fan sheets to dissipate heat build-up, thus preventing sheets from sticking together.

### **DocuColor 40/30 Family**

1. Load only 25 sheets in the BYPASS Tray or 250 sheets in the HIGH CAPACITY FEEDER\*\*.
2. Select ***Heavy Weight*** Mode.
3. Remove sheets from the output device after 50 sheets. Fan sheets to dissipate heat build-up, thus preventing sheets from sticking together.

### **DocuColor 12/ DocuCentre Color Series 50**

1. Load sheets in Tray 2, 3 or 4\*\*.
2. Select ***Heavy Weight*** Mode.
3. Remove sheets from the output device after 50 sheets. Fan sheets to dissipate heat build-up, thus preventing sheets from sticking together.

### **DocuColor 4**

1. Load only 25 sheets in the MULTI SHEET INSERTER\*\*.
2. Select ***Label*** Mode.
3. Remove sheets from the output device after 50 sheets. Fan sheets to dissipate heat build-up, thus preventing sheets from sticking together.

### **DocuColor 2045/60**

1. Load labels in Tray 3\*\*.
2. Select ***151-220 gsm*** Mode.
3. Remove sheets from the output device after 50 sheets. Fan sheets to dissipate heat build-up, thus preventing sheets from sticking together.

\*\* Refer to the product specific Recommended Materials List for proper paper handling instructions.

## ***TIPS***

- Fan sheets before loading.
- Store unused material in plastic polybag.
- When clearing a jam, carefully pull out the transfer drawer to avoid machine damage.
- Insure no labels have pre-dispensed.
- Limit toner saturation on electronic originals to a total of 240% saturation (60% for each color).

## ***FREE LABEL TEMPLATES***

### **Microsoft Word Compatible Templates**

- For 1 up label template, use AVERY 5165
- For 30 up label template, use AVERY 5160