

Installing the Machine

Installing the Developer Assembly and Drum Unit




CAUTION

To prevent damage or poor print quality, do not touch the green drum, or expose it to light for more than 3 minutes. Never expose the drum to direct sunlight

Note: If installing the optional paper tray assembly, it would be best done before loading supplies (machine is lighter). Go to *Paper Trays optional* in this chapter.


To install the Developer Assembly and Drum Unit:

1. Grasp the Top Cover Open Lever and open the top cover.




Installing the Machine

2. Hold the Developer Assembly with both hands and shake the cartridge back and forth several times. The following figure shows how to hold the developer assembly.




3. Holding the Developer Assembly with one hand, grasp the edge of the protective strip under the toner housing. Pull the strip firmly to completely remove it from the cartridge.




Installing the Machine

4. Position the Drum Unit with the green drum surface facing the black Toner Roller on the Developer Assembly. Without touching the green drum surface, hook the Drum Unit to the developer assembly. The following figure shows how to join the Drum Unit and the Developer Assembly.




Installing the Machine

5. Holding the Developer Assembly by the green handles, align the three shafts on the Developer Assembly sides with the slots in the machine frame. Lower the unit into the machine.




The following figure shows how the shafts on the Developer Assembly align with the slots.



Installing the Machine

6. Press firmly on the green squares on the Drum Unit until the Drum Unit clicks into place. The following figure shows how to press the Drum Unit into place.



7. Close the Top Cover. Press down on the Top Cover until a “click” is heard to ensure the cover is closed.

