Configuration page

The configuration page contains extensive information that is useful in Ethernet installation and troubleshooting network problems.

There are two ways to print the configuration page:

- Use the printer's rear panel switches.
 - **1.** Make sure **Switch 2**, **Switch 3**, and **Switch 4** are in the *down* position (the default position).
 - 2. Set Switch 4 up.

The printer prints the configuration page as soon as you set **Switch 4** *up*.

- **3**. When the configuration page has printed out, reset **Switch 4** to *down*.
- Send a PostScript language file to the printer.

The Phaser 480X CD-ROM and diskettes include a PostScript file for PCs (*PRNTCNFG.PS*) and a Macintosh utility (*Configuration Page*) for printing the configuration page.

Directions for using PC utilities

Directions for using the Macintosh utility

PC and workstation users

- 1. Locate the *PRNTCNFG.PS* file in the *PHSR480X* directory on either the Phaser 480X CD-ROM (*UTILS* directory) or on the Windows 3.1 Driver and Printer Utilities diskette.
- **2.** Copy the file to your hard disk, or use the file from the CD-ROM or diskette.
- 3. Use one of the following methods to send the file to the printer:
 - PC users: Use the DOS COPY command to send the *PRNTCNFG.PS* file to the printer. Or, use the Copy command in Windows File Manager to send the *PRNTCNFG.PS* file to the printer.
 - Workstation users: Send the *PRNTCNFG.PS* file to the printer as you would any PostScript file.

Macintosh users

- 1. Select the appropriate printer in the **Chooser**.
- 2. Locate the *Configuration Page* file and the *LaserWriter Utility* in the *Phaser 480X Utilities* folder on the Phaser 480X CD-ROM (*Utilities* folder) or on the Macintosh Printer Utilities diskette.
- **3.** Copy the files to your hard disk.
- **4.** Double-click on the **LaserWriter Utility** icon to start the application.
- 5. Choose **Download PostScript File** from the **Utilities** menu.
- 6. Select the *Configuration Page* file from the list, then click **Open**.
- 7. At the prompt Save PostScript output as: you are asked for a file name for saving printer output. Use either the default name given in the edit box or type a new name. Click **Save** to send the file to the printer.
- 8. If no output is returned by the printer, the *LaserWriter Utility* displays a dialog box. Click **OK** in the box to continue.