PHASER® 850
COLOR PRINTER

SETUP GUIDE

1 Placement

Place in well ventilated area

Level surface

2 cm (.75 in.) maximum

Allow clearance

10 cm (4 in.)

10 cm (4 in.)

30-minute cool down before moving printer

1.1

1.2

36 kg 79 lbs.

High-Capacity Paper Tray Assembly (option)

1.3

2 Add Ink

2.1

2.2

3 Connect Cables

Hard Drive (option)

Network Card (option)

Ethernet

Parallel

USB

USB connection: Macintosh or PC

Order A/B USB cable separately

Parallel connection: PC only

Use provided adapter, if necesssary

Order cable separately

Direct Ethernet connection: Macintosh or PC

Order hub and cables separately

4 Turn On Printer

Ready to Print

17 minute self-test/warmup

4.1

4.2

For network installation, see Software CD-ROM or tektronix.com/Color_Printers/support/

5 Load Media

5.1

5.2

Fill levels

Paper

Transparency

5.3

Transparency

Paper

5.4

High-Capacity Paper Tray Assembly (option)

Paper only

5.5

5.6

6 Load Software

Windows:
CD-ROM is auto-running, or run *start.exe*

Macintosh:
Double-click **Start Me First**

High-Capacity Paper Tray Assembly (option)

Copyright© 1999 by Tektronix. All Rights Reserved.
001-1275-00